

MAG ATF - 1
AUTOMATIC TRANSMISSION OIL

MAG ATF-1 is an automatic transmission fluid formulated from high quality of base oil and selected additives to meet ATF type A suffix A requirements and to provide good lubrication in automatic and semi-automatic transmission.

Specification

Meets General Motors TYPE A SUFFIX A.

Feature & Benefits

Provides excellent lubrication in automatic and semi-automatic transmission with low friction characteristic to meet GENERAL MOTORS Type A Suffix A requirements.

Additional Quality Features

1. It has good level of corrosion resistance and foam properties.
2. Very high viscosity index.
3. Very low pour point.
4. Friction properties to meet the requirements of type A Suffix A.

Application Of Use

MAG ATF-1 is recommended for automatic and semi-automatic and torque converters of passenger cars, light commercial vehicles when manufacturer requires an ATF meets GM TYPE A SUFFIX A.

Physical Characteristics	Test Method	Typical Value
Color	ASTM D-1500	Red
Density @ 15 °C, kg/L	ASTM D-1298	0.873
Kinematic Viscosity, cSt		
AT 40 °C	ASTM D-445	40.3
AT 100 °C	ASTM D-445	7.45
Viscosity Index	ASTM D-2270	150
Flash Point COC, °C	ASTM D-92	216
Pour Point, °C	ASTM D-97	-42
Brookfield Viscosity@-40°C, cP	ASTM D-2983	58000

Note: All figures may vary slightly.

No. 01. Feb. 2014