

MAG ATF - 2 AUTOMATIC TRANSMISSION OIL

MAG ATF-2 is a mineral based transmission fluid. Its formulated to provide smooth shifting in the automatic and semi-automatic transmission due to high quality of base oil and the additives used in the formulation.

Specification

Provides excellent lubrication in automatic and semi-automatic transmission, low friction characteristic to meet GENERAL MOTORS Dexron II requirements, Cat TO-2, Ford Mecron, DB236.6

Feature & Benefits

Provides excellent lubrication in automatic and semi-automatic transmission with low friction characteristic to meet GENERAL MOTORS DEXRON® II requirements.

Additional Quality Features

1. Smoother shift in transmission.
2. Very high viscosity index.
3. Very low pour point.
4. Friction properties to provide longer transmission life.
5. Single product for all types of automatic transmissions.

Application Of Use

Recommended for automatic and semi-automatic transmission and torque converters of passenger cars, light commercial vehicles, when the manufacturer requires an ATF Dexron II specification, it is also suitable for power steering system and hydraulic systems on farm tractors and heavy equipments.

Physical Characteristics	Test Method	Typical Value
Color	ASTM D-1500	Red
Density @ 15 °C, kg/L	ASTM D-1298	0.87
Kinematic Viscosity, cSt		
AT 40 °C	ASTM D-445	41
AT 100 °C	ASTM D-445	7.8
Viscosity Index	ASTM D-2270	165
Flash Point COC, °C	ASTM D-92	216
Pour Point, °C	ASTM D-97	-42
Brookfield Viscosity@-40°C, cP	ASTM D-2983	48000

Note: All figures may vary slightly.

No. 01. Feb. 2014