

MAG ULTRA 2 HD 50 SAE 50 DIESEL ENGINE OIL

ULTRA 2 HD 50 SAE 50 is a mono grade diesel engine oil, manufactured from a high quality of base oil and selected additives to give good protection. To provide excellent detergency and dispersancy. It has a good Quality alkalinity reserve to neutralized the acidic effect of high sulfur fuel for disel engine.

Feature & Benefits

It is specially formulated for mild conditions, it has a properties like anti-wear, anti-corrosion, anti-rust, and anti-oxidant.

Performance Level

API: CC/SC

Additional Quality Features

1. Protection against wear, rust and oxidation.
2. Excellent high temperature stability.
3. High stability in operation.

Application Of Use

ULTRA 2 HD 50 SAE 50 is recommended for use in diesel engines, for vehicles, trucks and vans operating under mild service conditions and for material handling machines.

CHARACTERISTICS	TEST METHOD	TYPICAL VALUE
SAE Grade		50
Density @ 15 °C, kg/L	ASTM D-1298	0.894
Kinematic Viscosity, cSt		
AT 40 °C cSt	ASTM D-445	214
AT 100 °C cSt	ASTM D-445	19.3
Viscosity Index	ASTM D-2270	102
Flash Point COC, °C	ASTM D-92	250
Pour Point, °C	ASTM D-97	-9

Note: All figures may vary slightly.

No. 01. Feb. 2014