

MAG SILK 3500 SAE 40 GASOLINE ENGINE OIL

SILK 3500 SAE 40 is a mono-grade gasoline engine oil, manufactured from a high quality of base oil and selected additives to give very good engine protection. It has formulated for mild conditions, it has the anti-wear, anti-corrosion, anti-rust, and anti-oxidant properties.

Features & Benefits

1. Protection against wear, rust and oxidation.
2. Excellent high temperature stability.
3. Good detergent, dispersant properties.

Specification:

Performance Level
 API: SF/CD
 MIL-L-46152 B

Application Of Use

SILK 3500 SAE 40 is recommended for use in gasoline and diesel engines, in passenger car operating under mild service conditions and for material handling machines.

Physical Characteristics	Test Method	Typical Value
SAE Grade		40
Density @ 15°C, Kg/L	ASTM D-1298	0.895
Kinematic Viscosity, cSt		
AT 40 °C cst	ASTM D-445	172.5
AT 100 °C cst	ASTM D-445	16
Viscosity Index	ASTM D-2270	102
Flash Point, COC, °C	ASTM D-92	250
Pour Point, °C	ASTM D-97	-9
TBN, mg KOH/gm	ASTM D-2896	7.0

Health & Safety:

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Note: All figures may vary slightly.

No. 01. Feb. 2014