

**MAG SILK 5000 SAE 20W-50
 GASOLINE ENGINE OIL**

MAG SILK 5000 SAE 20W-50 is a multi-grade gasoline and diesel engine oil manufactured from a high quality of base oil and selected additives to give very good engine protection. It has formulated for mild conditions, it has the anti-wear, anti-corrosion, anti-rust and anti-oxidant properties.

Features & Benefits

1. High thermal stability.
2. Perfect lubrication in all seasons.
3. Superior lubrication to reduce friction and has anti-wear, anti-corrosion properties.
4. Keep engine clean and cool even in high temperature.
5. Prevent parts sticking and consumption less oil.

Specification

Performance Level API: SG/CD

Application Of Use

MAG SILK 5000 SAE 20W-50 is suitable for use in gasoline and diesel engines, vehicles that are operating under tough service conditions in the city and high ways or bad roads.

Physical Characteristics	Test Method	Typical Value
SAE Grade		20W-50
Density @ 15°C, Kg/L	ASTM D-1298	0.89
Kinematic Viscosity, cSt		
AT 40 °C	ASTM D-445	178.5
AT 100 °C	ASTM D-445	19.8
Viscosity Index	ASTM D-2270	124
Apparent Viscosity @-15°C	ASTM D-5293	8900
Flash Point, COC, °C	ASTM D-92	240
Pour Point, °C	ASTM D-97	-24
TBN, mg KOH/g	ASTM D-2896	5

Note: All figures may vary slightly.

No. 01. Feb. 2014