

MAG SILK 7000 SAE 20W50 GASOLINE ENGINE OIL

MAG SILK 7000 SAE 20W50 is a multigrade gasoline engine oil, manufactured from a high quality of base oil and selected additives to formulate a multi-grade oil for all recent technology gasoline engines and light cars diesel engines. It is recommended for all modern gasoline engines running in severe conditions, on high ways and inside the cities, it has anti-wear, anti-corrosion, anti-rust and anti-oxidant properties, suitable for vehicles equipped with catalyts converter.

Features & Benefits:

1. Lubricants for all season.
2. Fully compatible with catalytic converter.
3. Superior lubrication, reduce fuel consumption and extended engine life.
4. Good for high speed driving on motorway as well as city drive.
5. Extended oil drain interval.
6. Easy starting on extremely cold weather.
7. Excellent thermal stability, good for operation in high temperature conditions.

Specification:

Performance Level API: SJ, MIL-L-2104E, ACEA A3-98 B3-98/E-3

Meets Requirements: MB 229.1, VW 505.00

Application Of Use:

MAG SILK 7 000 SAE 20W50 is recommended for modern gasoline and diesel engines, for vehicles equipped with catalyst converter for driving in the city and motorway. It is also recommended for use in turbo charged or naturally aspirated diesel engines in cars and light vans. Suitable for operation in all weather conditions.

Physical Characteristics	Test Method	Typical Value
SAE Grade		20W-50
Density @ 15°C Kg/L	ASTM D-1298	0.894
Kinematic Viscosity, cSt		
At 40°C cSt	ASTM D-445	165
At 100°C cSt	ASTM D-445	18.6
Viscosity Index	ASTM D-2270	127
Apparent Viscosity @-15°C	ASTM D-5293	9000
Flash Point, COC, °C	ASTM D-92	230
Pour Point, °C	ASTM D-97	-30
TBN, mg KOH/g	ASTM D-2896	8

Note: All figures may vary slightly.

No. 01. Feb. 2014