

MAG ULTRA 6 SUPER HD 40/50 DIESEL ENGINE OIL

ULTRA 6 SUPER HD 40/50 is a monograde diesel engine oil, manufactured from a high quality of base oil and selected additives to give excellent detergency and dispersancy.

Feature & Benefits

It is specially formulated for moderate conditions, it has a good quality alkalinity reserve to neutralize the acidic effect of high sulphur fuel for diesel engines.

Performance Level

API: CD/SF MIL-L-2104D
 MIL-L-46152B/C

Additional Quality Features

1. It has good level of detergency and disperancy.
2. Protection against wear and rust prevention.
3. Excellent high temperature stability.
4. Excellent internal engines cleanliness.
5. Excellent oxidation protection at high temperature.

Application Of Use

ULTRA 6 SUPER HD 40/50 is recommended for use in a diesel turbocharged and normally aspirated engines, for vehicle, trucks, buses and earth moving equipment operating on/off road and high ways and for material handling machines, generators.

CHARACTERISTICS	TEST METHOD	TYPICAL VALUE
SAE Grade		50
Density @ 15 °C, kg/L	ASTM D-1298	0.90
Kinematic Viscosity, cSt AT 40 °C AT 100 °C	ASTM D-445 ASTM D-445	178 17.50
Viscosity Index	ASTM D-2270	97
Flash Point COC, °C	ASTM D-92	245
Pour Point, °C	ASTM D-97	-9
TBN, mg KOH/gm	ASTM D-2896	10

Note: All figures may vary slightly.

No. 01. Feb. 2014