

**MAG SILK 4000 SAE 20W-50  
 GASOLINE ENGINE OIL**

**SILK 4000 SAE 20W-50** is a multigrade gasoline and diesel engine oil, manufactured from a high quality of base oil and selected additives to give very good engine protection. It has formulated for mild conditions, it has the anti-wear, anti-corrosion, anti-rust and anti-oxidant properties.

**Features & Benefits**

1. High thermal stability.
2. Perfect lubrication in all seasons.
3. Superior lubrication to reduce friction and has anti-wear, anti-corrosion properties.
4. Keep engine clean and cool, it is designed for high temperature weather.

**Specification**

Performance Level API: SF/CC, CCMCG2, MIL-L-46152 B.

**Application Of Use**

**SILK 4000 SAE 20W-50** is recommended for use in gasoline and diesel engines, for light buses and vans which are operating under tough service conditions in the city and high ways.

Physical Characteristics	Test Method	Typical Value
SAE Grade		20W50
Density @ 15°C, Kg/L	ASTM D-1298	0.89
Kinematic Viscosity, cSt		
AT 40 °C	ASTM D-445	180
AT 100 °C	ASTM D-445	19.85
Viscosity Index	ASTM D-2270	124
Apparent Viscosity @-15°C	ASTM D-5293	9000
Flash Point, COC, °C	ASTM D-92	245
Pour Point, °C	ASTM D-97	-24
TBN, mg KOH/g	ASTM D-2896	7

Note: All figures may vary slightly.

No. 01. Feb. 2014