

**MAG SILK 4500 SAE 20W-50
 GASOLINE ENGINE OIL**

MAG SILK 4500 SAE 20W-50 is a multi-grade diesel and gasoline engine oil, manufactured from a high quality of base oil and selected additives to give very good engine protection. It has formulated for mild conditions, it has the anti-wear, anti-corrosion, anti-rust and anti-oxidant properties.

Features & Benefits

1. High thermal stability.
2. Perfect lubrication in all seasons.
3. Superior lubrication to reduce friction and has anti-wear, anti-corrosion properties.
4. Keep engine clean and cool even in high temperature.
5. Prevent parts sticking and consumption less oil.

Specification

Performance Level API: SF/CD, CCMC G2, MIL-L-46152 B.

Application Of Use

MAG SILK 4500 SAE 20W-50 is suitable for use in diesel and gasoline engines, vehicles that are operating under tough service conditions in the city and high ways or bad roads.

Physical Characteristics	Test Method	Typical Value
SAE Grade		20W50
Density @ 15°C, Kg/L	ASTM D-1298	0.89
Kinematic Viscosity, cSt		
AT 40 °C	ASTM D-445	180
AT 100 °C	ASTM D-445	19.85
Viscosity Index	ASTM D-2270	130
Apparent Viscosity @-15°C	ASTM D-5293	9000
Flash Point, COC, °C	ASTM D-92	250
Pour Point, °C	ASTM D-97	-24
TBN, mg KOH/g	ASTM D-2896	8

Note: All figures may vary slightly.

No. 01. Feb. 2014