

## MAG ULTRA 1 SAE 40 DIESEL ENGINE OIL

**ULTRA 1 SAE 40** is a monograde diesel engine oil, manufactured from a high quality of base oil and selected additives to give good protection. To provide excellent detergency and dispersancy. It has a good quality alkalinity reserve to neutralized the acidic effect of high sulfur fuel for disel engine.

### Feature & Benefits

It is specially formulated for mild conditions, it has the anti-wear, anti-corrosion, anti-rust, and anti-oxidant properties.

### Performance Level

API: CC/SC

### Additional Quality Features:

1. Protection against wear and rust prevention.
2. Excellent high temperature stability.
3. High stability in operation.

### Application Of Use

**ULTRA 1 SAE 40** is recommended for use in diesel engines, for vehicles, vans and light trucks operating under mild service conditions and for material handling machines.

CHARACTERISTICS	TEST METHOD	TYPICAL VALUE
SAE Grade		40
Density @ 15 °C, kg/L	ASTM D-1298	0.894
Kinematic Viscosity, cSt		
AT 40 °C cSt	ASTM D-445	160
AT 100 °C cSt	ASTM D-445	15.5
Viscosity Index	ASTM D-2270	98
Flash Point COC, °C	ASTM D-92	245
Pour Point, °C	ASTM D-97	-6

Note: All figures may vary slightly.

No. 01. Feb. 2014