

MAG ULTRA 5 HD 40 SAE 40 DIESEL ENGINE OIL

ULTRA 5 HD 40 SAE 40 is a monograde heavy duty diesel engine oil, manufactured from a high quality of base oil and selected additives to give excellent detergency and dispersancy.

Feature & Benefits

It is specially formulated for moderate operating conditions, it has a good quality alkalinity reserve to neutralize the acidic effect of high sulphur fuel for diesel engines.

Performance Level

API: CD/SF MIL-L-2104D
 MIL-L-46152B/C

Additional Quality Features

1. It has good level of detergency and dispersancy.
2. Protection against wear and rust prevention.
3. Excellent high temperature stability.
4. Excellent internal engine cleanliness.
5. Excellent oxidation protection at high temperature.

Application Of Use

ULTRA 5 HD 40 SAE 40 is recommended for use in a heavy duty diesel engines, for vehicles trucks buses, vans operating on off road and high ways, material handling machines.

CHARACTERISTICS	TEST METHOD	TYPICAL VALUE
SAE Grade		40
Density @ 15 °C, kg/L	ASTM D-1298	0.896
Kinematic Viscosity, cSt AT 40 °C AT 100 °C	ASTM D-445	160 15.5
Viscosity Index	ASTM D-2270	97
Flash Point COC, °C	ASTM D-92	245
Pour Point, °C	ASTM D-97	-15
TBN, mg KOH/gm	ASTM D-2896	10

Note: All figures may vary slightly.

No. 01. Feb. 2014