

AQUALUB 4040 / SAE 40 TBN 40 MARINE OIL

MAG Aqualub 4040 is a trunk piston engine oils, it is formulated from high latest additives technology and high quality of base oils to meet the latest design of medium speed diesel engines burning residuals fuels in marine application and stationary engines.

Feature & Benefits

It is specially designed to provide a higher stress level during continuous operation. It provide engine outstanding cleanness in all weather conditions and longer engine life.

Performance Level

Exceeds API: CF

Additional Quality Features:

1. Excellent water resistance
2. Very good thermal and high temperature resistance.
3. Reduce build up deposits in the engine to provide reduction in the engine maintenance cost.
4. Double wear protection due to the oil film strength at high pressure during operation.
5. Very good viscosity control, oxidation resistance will less top-ups and no contamination with residual fuel.

Application of Use

Aqualub 4040 recommended for use in new modern marine and stationary medium & low speed Diesel Engines using high residual fuels and high sulphur content. It meets most of the engine manufacturer, WÄRTSILÄ, Caterpillar, Yanmar, Daihatsu and MAN Diesel.

CHARACTERISTICS	TEST METHOD	TYPICAL VALUE
SAE Grade		40
Density at 15 °C, g/cc	ASTM D 4052	0.921
Viscosity Index	ASTM D 2270	97
Kinematic viscosity at 40 °C	ASTM D 445	150
Kinematic viscosity at 100 °C	ASTM D 445	14.5
Flash Point (COC)	ASTM D 92	240
Pour Point °C	ASTM D 97	-15
TBN, mg-KOH/g	ASTM D 2896	40

Note: All figures may vary slightly.

No. 01. Feb. 2014